

Bussmann series GF BS88 Centre bolted tags



Product description

Eaton's Bussmann series range of British Standard C3 fuse links specifically designed for the protection of general industrial applications e.g. power distribution and cable protection.

Standard features

- Good peak let-through current limitation
- 1:1:6 Selective coordination ratio between "minor" and "major" fuse
- Power loss values well within the limits of IEC 60269

Catalogue symbol:

- GF(Amps)

Technical data:

- Rated voltage: 550 V a.c. / 250 V d.c.
- Rated current: 710 to 800 A
- Breaking capacity: 80 kA
- Class of operation: gG
- Size: C3

Standards/Approvals:

- BS88
- IEC 60269
- Suitable for use in RoHS compliant applications


Packaging:

- MOQ 1


Table 1. Technical data

Part number	Rated voltage	Rated current (Amps)	Energy integrals I²t (A²S)		Watts loss	Dimensions (mm)										Product class	Weight
			Pre-arcing	Total at 415 V a.c.		W	A	B	C	D	E	F	G	H	J		
GF710	550 V a.c. 250 V d.c.	710	3500	8100	53	210	185	80.5	10.5	15.5	25.4	134.5	83	9.5	gG	2.6Kg	
GF800	550 V a.c. 250 V d.c.	800	5000	11,500	64	210	185	80.5	10.5	15.5	25.4	134.5	83	9.5	gG	2.6Kg	

Outline drawing



Time current curve



Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions. Only order confirmations and technical documentation by Eaton is binding. Photos and pictures also do not warrant a specific layout or functionality. Their use in whatever form is subject to prior approval by Eaton. The same applies to Trademarks (especially Eaton, Moeller, and Cutler-Hammer). The Terms and Conditions of Eaton apply, as referenced on Eaton Internet pages and Eaton order confirmations.

Eaton
EMEA Headquarters
Route de la Longeraie 7
1110 Morges, Switzerland
Eaton.eu

© 2015 Eaton
All Rights Reserved
Publication No. 4103
June 2015