

stud-type terminal, clip-on (01 512)



Description

Article

Part No.: 01 512

stud-type terminal, clip-on

for cable lug, busbar 10 mm

M5

System

60Classic

100Energy

185mm-System

centre feed unit

Product group 07

Subgroup 28

pack size 25

EAN 4021267015121

Catalog page 2015 : 2/8, 3/1

eCl@ss 6.1 27141146
eCl@ss 7.1 27141146
ETIM 4.0 EC000001
ETIM 5.0 EC000001

Approvals

Standards

IEC 61439-1:2011

Approvals

Germanischer Lloyd



CCC approval: no certification required

Product data

Electrical data

Rated voltage (IEC) AC: 690 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 0.3 W.
(The power dissipation for operation with rated current would be 0.5 W.)

current carrying capacity (IEC) max.: 360 A

max. permitted voltage (IEC) AC: 1000 V

max. permitted voltage (IEC) DC: 1500 V

rated peak withstand current I_{pk} : 25.6 kA

Mechanical data

W x H x D: 18 x 24 x 25

Weight: 5 kg/100

for busbars: 12, 15, 20, 25, 30 x 10 sowie Doppel-T- und Dreifach-T-Profil

Screw M5, 8mm available length

Material properties

Connecting screws: screw +/- (PZ2), galvanized, chromized

Terminal body: steel, galvanized and chromized

Terminal body: nickel-plated Cu section

screw: hexagon screw with slot, galvanised, chromited

Version

Part no. 01 747 for 5mm thick busbars