


Adapter EPC 400 A, 4-pole (32 579)



Description

Article

Part No.: 32 579

EQUES® 60Classic

Adapter EPC 400 A, 4-pole
for Siemens 3VL400

185 x 300

System

60Classic

Product group 05

Subgroup 42

pack size 1

EAN 4021267325794

Catalog page 2015 : 2/36

eCl@ss 6.1 27370304
eCl@ss 7.1 27370304
ETIM 4.0 EC001531
ETIM 5.0 EC001531

Approvals

Standards

IEC 61439-1:2011

Approvals

CSA, UL



for UL feeder circuits >250V

Type number: EPC60630-L

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>

CSA file: 110285, CSA class: 3211-37 <http://directories.csa-international.org>

CCC approval: no certification required

Product data

Electrical data

Rated current (IEC): 400 A

Rated voltage (IEC) AC: 690 V

Rated current (UL): 630 A

Rated voltage (UL) AC: 600 V

rated isolation voltage U_i (AC): 800 V

Rated surge voltage U_{imp} : 6 kV

max. permitted voltage (IEC) AC: 800 V

max. permitted voltage (IEC) DC: 800 V

short-circuit withstandability: the MCCB gives the short-circuit protection to the adapter
SCCR: 30 kA

Mechanical data

W x H x D: 185 x 300 x 35

Weight: 350 kg/100

Poles: 4-polig

Material properties

Body: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 200,
halogen-free