



Part No.	type	cross section mm ²	width of terminal mm	width of braid w/o insulation mm	width of braid with insulation mm	thickness of terminal mm	length of terminal w/o insulation mm	diameter of terminal holes mm	distance center of hole to end of terminal mm	length between center of terminal holes mm	approximate weight kg	recommended current rating	
												A	A
62150323	UFLX 25-100-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	100	0.03	single 160	two parallel 260
62150523	ULFX 25-150-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	150	0.04	160	260
62151023	ULFX 25-200-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	200	0.05	160	260
62151523	ULFX 25-250-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	250	0.07	160	260
62151923	ULFX 25-300-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	300	0.08	160	260
62152323	ULFX 25-350-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	350	0.09	160	260
62152823	ULFX 25-400-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	400	0.10	160	260
62153323	ULFX 25-450-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	450	0.12	160	260
62153523	ULFX 25-500-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	500	0.13	160	260
62153823	ULFX 25-550-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	550	0.14	160	260
62154023	ULFX 25-600-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	600	0.15	160	260
62154523	ULFX 25-650-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	650	0.17	160	260
62155023	UFLX 25-700-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	700	0.18	160	260
62155523	UFLX 25-750-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	750	0.19	160	260
62156023	UFLX 25-800-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	800	0.20	160	260
62156523	UFLX 25-850-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	850	0.22	160	260
62156823	UFLX 25-900-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	900	0.23	160	260
62157523	UFLX 25-950-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	950	0.24	160	260
62158023	UFLX 25-1000-8/10	25	20	21	23	1.4	35	8,5 / 10,5	9	1000	0.25	160	260
62250323	UFLX 50-100-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	100	0.06	250	430
62250523	UFLX 50-150-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	150	0.08	250	430
62251023	UFLX 50-200-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	200	0.11	250	430
62251523	UFLX 50-250-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	250	0.13	250	430
62251920	UFLX 50-300-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	300	0.16	250	430
62252323	UFLX 50-350-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	350	0.18	250	430
62252823	UFLX 50-400-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	400	0.21	250	430
62253323	UFLX 50-450-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	450	0.23	250	430
62253523	UFLX 50-500-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	500	0.26	250	430
62253823	UFLX 50-550-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	550	0.28	250	430
62254023	UFLX 50-600-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	600	0.31	250	430
62254523	UFLX 50-650-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	650	0.33	250	430
62255023	UFLX 50-700-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	700	0.36	250	430
62255523	UFLX 50-750-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	750	0.38	250	430
62256023	UFLX 50-800-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	800	0.41	250	430
62256523	UFLX 50-850-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	850	0.43	250	430
62256823	UFLX 50-900-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	900	0.46	250	430
62257523	UFLX 50-950-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	950	0.48	250	430
62258023	UFLX 50-1000-8/10	50	20	21	23	2.9	35	8,5 / 10,5	9	1000	0.51	250	430

	type	cross section mm²	width of terminal mm	width of braid w/o insulation mm	width of braid with insulation mm	thickness of terminal mm	length of terminal w/o insulation mm	diameter of terminal holes mm	distance center of hole to end of terminal mm	length between center of terminal holes mm	approximate weight kg	recommended current rating A	recommended current rating A
Part No.		A	B	C	D	E	F	G/H	I/J	K		single	two parallel
	type	cross section mm²	width of terminal mm	width of braid w/o insulation mm	width of braid with insulation mm	thickness of terminal mm	length of terminal w/o insulation mm	diameter of terminal holes mm	distance center of hole to end of terminal mm	length between center of terminal holes mm	approximate weight kg	recommended current rating A	recommended current rating A
Part No.		A	B	C	D	E	F	G/H	I/J	K		single	two parallel
62550333	UFLX 100-100-10	100	20	21	23	5.9	35	8,5 / 10,5	9	100	0.12	390	680
62550530	UFLX 100-150-10	100	20	21	23	5.9	35	8,5 / 10,5	9	150	0.17	390	680
62551033	UFLX 100-200-10	100	20	21	23	5.9	35	8,5 / 10,5	9	200	0.22	390	680
62551533	UFLX 100-250-10	100	20	21	23	5.9	35	8,5 / 10,5	9	250	0.27	390	680
62551933	UFLX 100-300-10	100	20	21	23	5.9	35	8,5 / 10,5	9	300	0.32	390	680
62552333	UFLX 100-350-10	100	20	21	23	5.9	35	8,5 / 10,5	9	350	0.37	390	680
62552833	UFLX 100-400-10	100	20	21	23	5.9	35	8,5 / 10,5	9	400	0.42	390	680
62553333	UFLX 100-450-10	100	20	21	23	5.9	35	8,5 / 10,5	9	450	0.47	390	680
62553533	UFLX 100-500-10	100	20	21	23	5.9	35	8,5 / 10,5	9	500	0.52	390	680
62553833	UFLX 100-550-10	100	20	21	23	5.9	35	8,5 / 10,5	9	550	0.57	390	680
62554033	UFLX 100-600-10	100	20	21	23	5.9	35	8,5 / 10,5	9	600	0.62	390	680
62554533	UFLX 100-650-10	100	20	21	23	5.9	35	8,5 / 10,5	9	650	0.67	390	680
62555033	UFLX 100-700-10	100	20	21	23	5.9	35	8,5 / 10,5	9	700	0.72	390	680
62555533	UFLX 100-750-10	100	20	21	23	5.9	35	8,5 / 10,5	9	750	0.77	390	680
62556033	UFLX 100-800-10	100	20	21	23	5.9	35	8,5 / 10,5	9	800	0.82	390	680
62556533	UFLX 100-850-10	100	20	21	23	5.9	35	8,5 / 10,5	9	850	0.87	390	680
62556833	UFLX 100-900-10	100	20	21	23	5.9	35	8,5 / 10,5	9	900	0.92	390	680
62557533	UFLX 100-950-10	100	20	21	23	5.9	35	8,5 / 10,5	9	950	0.97	390	680
62558033	UFLX 100-1000-10	100	20	21	23	5.9	35	8,5 / 10,5	9	1000	1.02	390	680
62650333	UFLX 120-100-10	120	32	33	35	4.4	35	10,5 / 12,5	12	100	0.14	450	780
62650533	UFLX 120-150-10	120	32	33	35	4.4	35	10,5 / 12,5	12	150	0.20	450	780
62651033	UFLX 120-200-10	120	32	33	35	4.4	35	10,5 / 12,5	12	200	0.26	450	780
62651533	UFLX 120-250-10	120	32	33	35	4.4	35	10,5 / 12,5	12	250	0.32	450	780
62651933	UFLX 120-300-10	120	32	33	35	4.4	35	10,5 / 12,5	12	300	0.38	450	780
62652333	UFLX 120-350-10	120	32	33	35	4.4	35	10,5 / 12,5	12	350	0.44	450	780
62652833	UFLX 120-400-10	120	32	33	35	4.4	35	10,5 / 12,5	12	400	0.50	450	780
62653333	UFLX 120-450-10	120	32	33	35	4.4	35	10,5 / 12,5	12	450	0.56	450	780
62653533	UFLX 120-500-10	120	32	33	35	4.4	35	10,5 / 12,5	12	500	0.62	450	780
62653833	UFLX 120-550-10	120	32	33	35	4.4	35	10,5 / 12,5	12	550	0.68	450	780
62654033	UFLX 120-600-10	120	32	33	35	4.4	35	10,5 / 12,5	12	600	0.74	450	780
62654533	UFLX 120-650-10	120	32	33	35	4.4	35	10,5 / 12,5	12	650	0.80	450	780
62655033	UFLX 120-700-10	120	32	33	35	4.4	35	10,5 / 12,5	12	700	0.86	450	780
62655533	UFLX 120-750-10	120	32	33	35	4.4	35	10,5 / 12,5	12	750	0.92	450	780
62656033	UFLX 120-800-10	120	32	33	35	4.4	35	10,5 / 12,5	12	800	0.98	450	780
62656533	UFLX 120-850-10	120	32	33	35	4.4	35	10,5 / 12,5	12	850	1.04	450	780
62656833	UFLX 120-900-10	120	32	33	35	4.4	35	10,5 / 12,5	12	900	1.10	450	780
62657533	UFLX 120-950-10	120	32	33	35	4.4	35	10,5 / 12,5	12	950	1.16	450	780
62658033	UFLX 120-1000-10	120	32	33	35	4.4	35	10,5 / 12,5	12	1000	1.22	450	780
62850333	UFLX 240-100-10	240	32	33	35	8.9	35	10,5 / 12,5	12	100	0.28	700	1150
62850533	UFLX 240-150-10	240	32	33	35	8.9	35	10,5 / 12,5	12	150	0.40	700	1150
62851033	UFLX 240-200-10	240	32	33	35	8.9	35	10,5 / 12,5	12	200	0.52	700	1150
62851533	UFLX 240-250-10	240	32	33	35	8.9	35	10,5 / 12,5	12	250	0.64	700	1150
62851933	UFLX 240-300-10	240	32	33	35	8.9	35	10,5 / 12,5	12	300	0.76	700	1150
62852333	UFLX 240-350-10	240	32	33	35	8.9	35	10,5 / 12,5	12	350	0.88	700	1150
62852833	UFLX 240-400-10	240	32	33	35	8.9	35	10,5 / 12,5	12	400	1.00	700	1150
62853333	UFLX 240-450-10	240	32	33	35	8.9	35	10,5 / 12,5	12	450	1.12	700	1150
62853533	UFLX 240-500-10	240	32	33	35	8.9	35	10,5 / 12,5	12	500	1.24	700	1150
62853833	UFLX 240-550-10	240	32	33	35	8.9	35	10,5 / 12,5	12	550	1.36	700	1150
62854033	UFLX 240-600-10	240	32	33	35	8.9	35	10,5 / 12,5	12	600	1.48	700	1150
62854533	UFLX 240-650-10	240	32	33	35	8.9	35	10,5 / 12,5	12	650	1.60	700	1150
62855033	UFLX 240-700-10	240	32	33	35	8.9	35	10,5 / 12,5	12	700	1.72	700	1150
62855533	UFLX 240-750-10	240	32	33	35	8.9	35	10,5 / 12,5	12	750	1.84	700	1150
62856033	UFLX 240-800-10	240	32	33	35	8.9	35	10,5 / 12,5	12	800	1.96	700	1150
62856533	UFLX 240-850-10	240	32	33	35	8.9	35	10,5 / 12,5	12	850	2.08	700	1150
62856833	UFLX 240-900-10	240	32	33	35	8.9	35	10,5 / 12,5	12	900	2.20	700	1150
62857533	UFLX 240-950-10	240	32	33	35	8.9	35	10,5 / 12,5	12	950	2.32	700	1150
62858033	UFLX 240-1000-10	240	32	33	35	8.9	35	10,5 / 12,5	12	1000	2.44	700	1150